



Technical Information



Inner bore <i>d</i> mm	Bearing number		Principal dimensions			Basic load ratings		Max runout speed		Mass kg
	cylindrical bore	tapered bore	<i>D</i>	<i>W</i> mm	<i>r</i>	dynamic <i>C</i> N	static <i>C₀</i>	grease oil	r/min	
10	2200		30	14	0.6	6400	1300	15400	19600	0.470
12	2201		32	14	0.6	6800	1500	14000	18200	0.530
15	2202		35	14	0.6	6900	1600	12600	15400	0.060
17	2203		40	16	0.6	8400	2000	11900	14000	0.088
20	2204		47	18	1.0	13400	3300	9800	11900	0.140
25	2205	2205 K	52	18	1.0	13400	3500	7700	9800	0.160
30	2206	2206 K	62	20	1.0	19000	5300	6600	8400	0.260
35	2207	2207 K	72	23	1.1	24500	7000	5900	7000	0.400
40	2208	2208 K	80	23	1.1	25500	8000	5200	6300	0.510
45	2209	2209 K	85	23	1.1	26000	8400	4900	5900	0.550
50	2210	2210 K	90	23	1.1	27000	8900	4400	5200	0.600
55	2211	2211 K	100	25	1.5	31200	10700	4200	4900	0.810
60	2212	2212 K	110	28	1.5	39000	13600	3700	4400	1.100
65	2213	2213 K	120	31	1.5	45700	16000	3500	4200	1.450
70	2214		125	31	1.5	35300	13600	3300	3900	1.500
75	2215	2215 K	130	31	1.5	35300	14400	3100	3700	1.600
80	2216	2216 K	140	33	2.0	52000	20400	2800	3300	2.000
85	2217	2217 K	150	36	2.0	46800	18800	2600	3100	2.500
90	2218	2218 K	160	40	2.0	56100	22800	2500	3000	3.400

